



# DIMENSIONS - FLOATING BALL VALVE

## Class 600 Lbs

DN (in)	A			Bø	C	D	Kg	Torque (Nm)
	RF	BW	RTJ					
0.5	165	165	163,5	14	145	82	5	18
0.75 x 0.50	190,5	190,5	190,5	14	145	82	7	18
0.75	190,5	190,5	190,5	20	170	87	7	21
1.00 x 0.75	216	216	216	20	170	87	9	21
1.00	216	216	216	25	170	92	10	45
1.25 x 1.00	228,5	228,5	228,5	25	170	92	14	45
1.25	228,5	228,5	228,5	32	270	105	15	80
1.50 x 1.25	241,5	241,5	241,5	32	270	105	17	80
1.50	241,5	241,5	241,5	38	270	108	18	91
2.00 x 1.50	292	292	295	38	270	108	20	91
2.00	292	292	295	50	270	119	22	125
2.50 x 2.00	330	330	330	50	270	119	27	125
2.50	330	330	330	65	380	150	28	140
3.00 x 2.00	355,5	355,5	358,5	65	270	119	33	125
3.00	355,5	355,5	338,5	76	380	163	38	195
4.0 x 3.00	432	432	435	76	380	163	75	195
4.00	432	432	435	102	470	187	78	350
6.00 x 4.00	559	559	562	102	470	187	150	350

All dimensions are in millimetres

## Class 900/1500 Lbs

DN (in)	A			Bø	C	D	Kg	Torque (Nm)	
	RF	BW	RTJ					Class 900	Class 1500
0.5	216	216	216	14	145	82	10	21	35
0.75 x 0.50	229	229	229	14	145	82	11	21	35
0.75	229	229	229	20	170	87	14	33	42
1.00 x 0.75	254	254	254	20	170	87	15	33	42
1.00	254	254	254	25	170	92	17	68	120
1.25 x 1.00	279,5	279,5	279,5	25	170	92	19	68	120
1.25	279,5	279,5	279,5	32	270	105	23	90	250
1.50 x 1.25	305	305	305	32	270	105	25	90	250
1.50	305	305	305	38	270	108	28	135	305
2.00 x 1.50	368	368	371	38	270	108	30	135	305
2.00	368	368	371	50	270	119	34	189	390

All dimensions are in millimetres



Ensuring your control on the flow...